外国政府による けしからん (素晴らしい) インターネット検閲システム (GFW 等) に対抗すれば、双方の技術力が進歩して大変良い

如果日本以外的政府建立了GFW这样的审查系统，而我们日本人建立了反制系统，那么两国的网络技术将迅速进步，这是一件非常好的事情。

Bypassing Government's Censorship Firewall: A Great Firewall Cat-and-Mouse Game in Cyberspace.

2021/07/16 JANOG48 Meeting - インターネット(遮)断

登大遊 (Daiyuu Nobori, Ph.D.)

- 本日の発表内容は、登が2012年～2015年ごろに筑波大学で行っていた研究をベースとしています。少し古い内容ですが、ご了承をお願いします。
- 本研究は、独立した研究者の活動であり、私が現在所属している各組織の立場とは無関係です。

第1章

外国政府による インターネット検閲の手法

(インターネット検閲先進国・中国の
素晴らしい偉大な作品 “GFW” の例)

あゝ素晴らしい GFW (Great Firewall)

伝統の味わひ

国家的巨型防火墙。在技术上非常好其研究和开发能力值得称赞。

GFW が市民に提供する主な遮断サービス

- 第1世代 (2000年代～)
 - 海外の特定 IP アドレスを対象とした遮断
 - 数千個が限界、共有Webサーバー等でトラブルが発生する
- 第2世代 (2000年代～)
 - 偽装 DNS、TCP、SMTP パケットを応答させることによるコネクション遮断
 - 上限がないが DNS および TCP しか対応できない
- 第3世代 (2014年6月～)
 - 第1世代を拡張。大量の海外 IP アドレスへの動的フィルタリング機能を搭載
 - 各 L2 スイッチの TCAM (Ternary CAM) が溢れないようにするため 180 秒間のみ ACL を挿入する手法を開発

• 第1世代 (2000年代～)

• 海外の特定 IP アドレスを対象とした遮断

- 数千個が限界、共有Webサーバー等でトラブルが発生する

```
管理: C:\Windows\system32\cmd.exe - tracert -d 130.158.6.57
C:\>tracert -d 130.158.6.57

130.158.6.57 へのルートをトレースしています。経由するホップ数は最大 30 です

  1  <1 ms    <1 ms    <1 ms    10.132.48.62
  2   1 ms     1 ms     <1 ms    10.132.29.2
  3   2 ms     2 ms     1 ms    140.206.149.97
  4   4 ms     3 ms     3 ms    140.206.149.245
  5   6 ms     4 ms     3 ms    139.226.196.77
  6   *        *        *        要求がタイムアウトしました。
  7   7 ms     7 ms     7 ms    219.158.9.209
  8   7 ms     7 ms     7 ms    219.158.97.94
  9   *        *        *        要求がタイムアウトしました。
 10  *        *        *        要求がタイムアウトしました。
 11  *        *        *        要求がタイムアウトしました。
 12  *        *        *        要求がタイムアウトしました。
 13  *        *        *        要求がタイムアウトしました。
 14  *        *        *        要求がタイムアウトしました。
```

• 第2世代 (2000年代~)

- 偽装 DNS、TCP、SMTP パケットを応答させることによる
コネクション遮断
 - 上限がないが DNS および TCP しか対応できない

TCP 実験例

```
telnet 130.158.83.218 80
GET /search?q=%E5%85%AD%E5%9B%9B
HTTP/1.1
HOST: penguin1.cs.tsukuba.ac.jp
```

六四 |

中国側クライアントPC

Intel(R) PRO/1000 MT Network Connection: ¥Device¥NPF_{C995C203-4743-40B3-A58D-742B828F2D0E} [Wireshark 1.8.3 (SVN Rev 45256 from /trunk-1.8)]

Filter: ip.addr==130.158.83.218

No.	Time	Source	Destination	Protocol	Length	Info
27831	17:20:31.597191000	10.132.48.3	130.158.83.218	TCP	66	64414 > http [SYN] Seq=0 win=8192 Len=0 MSS=1460 WS=256
27850	17:20:31.651964000	130.158.83.218	10.132.48.3	TCP	66	http > 64414 [SYN, ACK] Seq=0 Ack=1 win=8192 Len=0 MSS=1460 WS=256
27851	17:20:31.651993000	10.132.48.3	130.158.83.218	TCP	54	64414 > http [ACK] Seq=1 Ack=1 win=65536 Len=0
27855	17:20:31.658501000	10.132.48.3	130.158.83.218	TCP	55	[TCP segment of a reassembled PDU]
27883	17:20:31.741053000	10.132.48.3	130.158.83.218	TCP	60	http > 64414 [ACK] Seq=1 Ack=2 win=13128 Len=0
27883	17:20:31.741053000	10.132.48.3	130.158.83.218	HTTP	117	GET /search?q=%E5%85%AD%E5%9B%9B HTTP/1.1
27893	17:20:31.786024000	130.158.83.218	10.132.48.3	TCP	60	http > 64414 [RST] Seq=1 win=964096 Len=0

Frame 27883: 117 bytes on wire (936 bits)
Ethernet II, Src: vmware_81:41:4d (00:50:56:81:41:4d), Dst: Intel_14:a2:0f (00:14:a2:0f:14:a2:0f), Dst: Microsoft_01:41:0d (00:15:5d:01:41:0d)
Internet Protocol Version 4, Src: 10.132.48.3, Dst: 130.158.83.218
Transmission Control Protocol, Src Port: 64414, Dst Port: http (80), Seq: 1, Ack: 1, Len: 63
[2 Reassembled TCP Segments (64 bytes): #440(1), #442(63)]
Hypertext Transfer Protocol
GET /search?q=%E5%85%AD%E5%9B%9B HTTP/1.1
[Expert Info (Chat/Sequence): GET /search?q=%E5%85%AD%E5%9B%9B HTTP/1.1
Request Method: GET
Request URI: /search?q=%E5%85%AD%E5%9B%9B
Request Version: HTTP/1.1
HOST: cn.bing.com\r\n\r\n
[Full request URI: http://cn.bing.com/search?q=%E5%85%AD%E5%9B%9B]

Microsoft Corporation: ¥Device¥NPF_{55DC283B-1CDE-44DF-A3B2-7BEE98411646} [Wireshark 1.8.3 (SVN Rev 4...)]

Filter: ip.addr==140.206.86.76

No.	Time	Source	Destination	Protocol	Length	Info
437	35.2581490	140.206.86.76	130.158.83.218	TCP	66	64414 > http [SYN] Seq=0 win=8192 Len=0 MSS=1460 WS=256
438	35.2582020	130.158.83.218	140.206.86.76	TCP	66	http > 64414 [SYN, ACK] Seq=0 Ack=1 win=8192 Len=0 MSS=1460 WS=256
439	35.3114200	140.206.86.76	130.158.83.218	TCP	60	64414 > http [ACK] Seq=1 Ack=1 win=65536 Len=0
440	35.3178830	140.206.86.76	130.158.83.218	TCP	60	[TCP segment of a reassembled PDU]
442	35.3998610	140.206.86.76	130.158.83.218	HTTP	117	GET /search?q=%E5%85%AD%E5%9B%9B HTTP/1.1
443	35.4017760	140.206.86.76	130.158.83.218	TCP	60	64414 > http [RST] Seq=65 win=16594688 Len=0

Frame 442: 117 bytes on wire (936 bits), 117 bytes captured (936 bits) on interface 0
Ethernet II, Src: Nortel_14:a2:0f (00:14:a2:0f:14:a2:0f), Dst: Microsoft_01:41:0d (00:15:5d:01:41:0d)
Internet Protocol Version 4, Src: 140.206.86.76 (140.206.86.76), Dst: 130.158.83.218 (130.158.83.218)
Transmission Control Protocol, Src Port: 64414 (64414), Dst Port: http (80), Seq: 2, Ack: 1, Len: 63
[2 Reassembled TCP Segments (64 bytes): #440(1), #442(63)]
Hypertext Transfer Protocol
GET /search?q=%E5%85%AD%E5%9B%9B HTTP/1.1\r\n
[Expert Info (Chat/Sequence): GET /search?q=%E5%85%AD%E5%9B%9B HTTP/1.1\r\nRequest Method: GET
Request URI: /search?q=%E5%85%AD%E5%9B%9B
Request Version: HTTP/1.1
HOST: cn.bing.com\r\n\r\n
[Full request URI: http://cn.bing.com/search?q=%E5%85%AD%E5%9B%9B]

日本側サーバーPC

Government's Firewall

DNS 実験例

```
管理者: C:\Windows\system32\cmd.exe - nslookup
> twitter.com.
サーバー: google-public-dns-a.google.com
Address: 8.8.8.8

権限のない回答:
名前:    twitter.com
Address: 59.24.3.173

> twitter.com.
サーバー: google-public-dns-a.google.com
Address: 8.8.8.8

権限のない回答:
名前:    twitter.com
Address: 37.61.54.158

> twitter.com.
サーバー: google-public-dns-a.google.com
Address: 8.8.8.8

権限のない回答:
名前:    twitter.com
Address: 37.61.54.158

> .
```

中国側クライアントPC

No.	Time	Source	Destination	Protocol	Length	Info
8166	17:28:52.367949000	130.158.83.218	10.132.48.3	DNS	87	standard query response 0x003a A 59.24.3.173
8171	17:28:52.399875000	130.158.83.218	10.132.48.3	DNS	135	standard query response 0x003a A 199.59.149.198

Frame 8166: 87 bytes on wire (696 bits), Ethernet II, Src: Cisco_5f:26:5f (6c:20:00:00:5f:26:5f), Dst: Nortel_14:a2:0f (00:1a:8f:14:a2:0f), Internet Protocol Version 4, Src: 130.158.83.218 (130.158.83.218), Dst: 10.132.48.3 (10.132.48.3), User Datagram Protocol, Src Port: domain, Destination Port: 57862, Domain Name System (response)

- [Request In: 8157]
- [Time: 0.036163000 seconds]
- Transaction ID: 0x003a
- Flags: 0x8180 Standard query response, Questions: 1, Answer RRs: 1, Authority RRs: 0, Additional RRs: 0
- Queries
- Answers
 - twitter.com: type A, class IN, addr

```
0000 00 50 56 81 41 4d 6c 20 56 5f 26 5f
0010 00 49 95 3c 00 00 36 11 de 58 82 9e
0020 30 03 00 35 e2 06 00 35 ef bc 00 3a
0030 00 01 00 00 00 00 07 74 77 69 74 74
0040 6f 6d 00 00 01 00 01 c0 0c 00 01 00
0050 f5 00 01 3b 18 02 2d
```

日本側サーバーPC

No.	Time	Source	Destination	Protocol	Length	Info
25	2.029306000	130.158.83.218	140.206.86.76	DNS	135	standard query response 0x003a A 199.59.149.198 A 199.59.149.198

Frame 25: 135 bytes on wire (1080 bits), 135 bytes captured (1080 bits) on interface 0, Ethernet II, Src: Microsof_01:41:0d (00:15:5d:01:41:0d), Dst: Nortel_14:a2:0f (00:1a:8f:14:a2:0f), Internet Protocol Version 4, Src: 130.158.83.218 (130.158.83.218), Dst: 140.206.86.76 (140.206.86.76), User Datagram Protocol, Src Port: domain (53), Dst Port: 57862 (57862), Domain Name System (response)

- [Request In: 24]
- [Time: 0.000095000 seconds]
- Transaction ID: 0x003a
- Flags: 0x8180 Standard query response, No error, Questions: 1, Answer RRs: 4, Authority RRs: 0, Additional RRs: 0
- Queries
- Answers
 - twitter.com: type A, class IN, addr 199.59.149.198
 - Name: twitter.com
 - Type: A (Host address)

Government's Firewall

2014/1/21 に GFW の DNS 偽装応答システムで大規模誤作動が発生！

```
> www.yahoo.com.  
サーバー: google-public-dns-a.google.  
Address: 8.8.8.8
```

権限のない回答:

```
名前: ds-fp3.wg1.b.yahoo.com  
Address: 65.49.2.178  
Aliases: www.yahoo.com  
fd-fp3.wg1.b.yahoo.com
```

```
> www.ascii.co.jp.
```

```
サーバー: google-public-dns-a.google.  
Address: 8.8.8.8
```

権限のない回答:

```
名前: www.ascii.co.jp  
Address: 65.49.2.178
```

```
> www.tsukuba.ac.jp.
```

```
サーバー: google-public-dns-a.google.  
Address: 8.8.8.8
```

権限のない回答:

```
名前: www.tsukuba.ac.jp  
Address: 65.49.2.178
```

```
> www.microsoft.com.
```

```
サーバー: google-public-dns-a.google.com  
Address: 8.8.8.8
```

権限のない回答:

```
名前: lb1.www.ms.akadns.net  
Address: 65.49.2.178  
Aliases: www.microsoft.com  
toggle.www.ms.akadns.net  
g.www.ms.akadns.net
```

2014年中国网络异常事件 [编辑]

2014年中国网络异常事件指的是2014年1月21日下午发生在中国的大范围网络故障事件。由于中国通用顶级域名解析出现异常,许多网站域名被解析到了完全没有反应的IP地址65.49.2.178。IP地址65.49.2.178由位于美国北卡罗来纳州的Dynamic Internet Technology公司所拥有,该公司开发了自由门等翻墙软件,因此事件被认为可能是一次黑客攻击,但该公司否认攻击。

经过 [编辑]

1月21日上午9时,腾讯问题。^[3]

1月21日15时10分左右地址65.49.2.178,全部恢复正常,但完全消

FACTA ONLINE

ログイン | マイページ | オンライン会員登録 | オンライン版について

SEARCH

HOME ARCHIVES FREE BLOG SHARE FORUM

中国が「ネット長城」通信障害で真っ赤な嘘

2014年3月号

PRINT SHARE ツイート 1 1 0

1月21日、中国のインターネットに未曾有の通信障害が発生した。中国国内の端末からウェブサイトに接続しようとする通信エラーになり、多数のサイトが閲覧不能になったのだ。

通信障害は中国時間午後3時過ぎに始まり、2時間ほど続いた。その間、ネット空間は事実上のマヒ状態に陥った。検索大手の「百度(バイドウ)」や中国版ツイッターの「微博(ウェイボー)」などの人気サービスも利用できなくなり、影響を受けたユーザーは数億人にのぼるとみられる。

翌22日、政府系ネットセキュリティ研究機関の国家互連網応急センター(CNCERT)は、「国内のルートDNS(Dメインネームシステム)サーバーが何者かに攻撃されたのが原因」と発表した。DNSとは「facta.co.jp」のように文字列で表記されたホスト名を「202.210.142.113」のように数字で表記されるIPアドレスに変換するシステムのことだ。

China Unicom 社のトランジットを契約し、 GFW 遮断を「故障」(= SLA 契約違反) として China Unicom 社に申告し、 修理を依頼してみる実験

China Unicom 社からの 正式回答

- 「該当IPアドレスの疎通の問題については回答できかねる」

けしからん、けしからん やっつけないと いけない

筑波大学
University of Tsukuba

技術力

第2章 VPN Gate

けしからん政府の検閲用ファイアウォールを回避するための大規模分散型 VPN 中継システム

VPN Gate の概要

- インターネット検閲用ファイアウォール
 - Great Firewall of China (GFW) が有名。
- 政府による検閲用ファイアウォールを回避する方法として、中継サーバを利用する手法がある。
- 中継サーバは、ファイアウォールの内側のユーザが、自由にインターネットにアクセスする際の経由点となる。
 - 公開 VPN 中継サーバ
 - オープンプロキシ
 - Tor ノード

既存の中継サーバの問題点

- 検閲当局も、中継サーバの IP アドレスを入手することができてしまう。

関連研究: 検閲用ファイアウォール回避システム

- 遮断耐性の強化に関する研究:
 - Web MIXes [Berthold 2001]
 - Ignoring the Great Firewall of China [Clayton 2006]
 - Infranet [Feamster 2002]
 - Thwarting web censorship with untrusted messenger discovery [Feamster 2003]
 - How to achieve blocking resistance for existing systems enabling anonymous web surfing [Köpsell 2004]
- 検閲当局が発信している調査用パケットに関するもの:
 - Great Firewall Tor probing Circa 09 [Wilde 2011]
 - How the great firewall of china is blocking Tor [Winter 2012]

VPN Gate の遮断耐性実現手法

1. 数千のボランティアによる中継サーバの稼働
 - 検閲当局はすべての IP アドレスを遮断しなければならなくなる。

ボランティアの組織化をする手法

VPN Gate の遮断耐性実現手法

1. 数千のボランティアによる中継サーバの稼働
 - 検閲当局はすべての IP アドレスを遮断しなければならない。
2. 無実の IP アドレスの混入手法
 - 検閲当局はすべての IP アドレスを検証しなければならない。

無実の IP アドレスの混入

Innocent IP mixing

検閲当局による調査パケットの発信

VPN Gate の遮断耐性実現手法

1. 数千のボランティアによる中継サーバの稼働
 - 検閲当局はすべての IP アドレスを遮断しなければならなくなる。
2. 無実の IP アドレスの混入手法
 - 検閲当局はすべての IP アドレスを検証しなければならなくなる。
3. 協調的スパイ発見手法
 - 検閲当局は IP アドレスの検証活動ができなくなる。

協調的スパイ発見手法

実装

VPN Gate Server ソフトウェア

VPN Gate Service Control Panel

VPN Gate
An Academic Experiment
Public VPN Relay Servers
Hosted by Volunteers

Firewall
Out of Order
by Unknown
Reason

Bypass FW

Liberty!!

VPN Gate Client
Domestic Internet

Target Servers
Overseas Internet

www.vpngate.net

An Academic Experiment
@ Graduate School of
University of Tsukuba, Japan.
www.tsukuba.ac.jp/english/

YouTube
twitter

Join the VPN Gate Academic Research Project? [Browse http://www.vpngate.net/ ...](http://www.vpngate.net/)

VPN Gate is an academic experiment for the research on the 'Distributed Public VPN Relay Server' technology, operated at the Graduate School on University of Tsukuba, Japan. VPN Gate Client users can connect to VPN Gate Services running on Public VPN Relay Servers, and enjoy unrestricted Internet access via the VPN Relay Server.

When a VPN Gate Client user accesses to a server on Internet, the source IP address will be replaced to the IP address of the relaying Public VPN Server. Consequently, the VPN Gate Client user will be able to browse overseas web sites smoothly even if the user's local firewall is out of order by an unknown reason and unable to pass such an access.

Enable the VPN Gate Relay Service and Join the VPN Gate Research as a Volunteer.

i If you check the above checkbox and press OK, the VPN Gate Relay Service will be activated on this computer. As the result, any VPN Gate Client will be able to communicate towards the Internet via the VPN Gate Relay Service. It is secure even if your computer is on the private network (e.g. corporate network) because any accesses to private IP addresses will not be permitted to pass via the VPN Gate Relay Service.

OK Cancel

VPN Gate リストサーバ (ディレクトリサーバ)

The 5582 Public VPN Relay Servers by volunteers around the world.

You may connect to any of these VPN servers with: Username: 'vpn', Password: 'vpn'.

Apply search filters: SoftEther VPN (SSL-VPN) L2TP/IPsec OpenVPN MS-SSTP (Add your VPN server to this list.)

You must specify the IP address of the destination VPN Server, instead of DDNS hostname (.opengw.net) if you are under censorship.

Do you want to parse the below HTML table? Instead you can use [CSV List](#) to make your own VPN Gate client app.

計算された
スコア

Country (Physical location)	DDNS hostname IP Address (ISP hostname)	VPN sessions Uptime Cumulative users	Line quality Throughput and Ping Cumulative transfers Logging policy	SSL-VPN Windows (comfortable)	L2TP/IPsec Windows, Mac, iPhone, Android No client required	OpenVPN Windows, Mac, iPhone, Android	MS-SSTP Windows Vista, 7, 8, RT No client required	Volunteer operator's name (+ Operator's message)	Score (Quality)
Japan	vpn531776102.opengw.net 133.209.98.57 (FL1-133-209-98-57.tky.mesh.ad.jp)	50 sessions 11 hours Total 33,041 users	189.59 Mbps Ping: 37 ms 3,853.09 GB Logging policy: 2 Weeks	✓ SSL-VPN Connect guide TCP: 1649 UDP: Supported		✓ OpenVPN Config file TCP: 1649 UDP: 1646	✓ MS-SSTP Connect guide SSTP Hostname : vpn531776102.o pengw.net:1649	By kohdaNECuser-PC's own er	531,864
Korea Republic of	vpn169867300.opengw.net 211.217.143.231	30 sessions 17 hours Total 5,245 users	80.80 Mbps Ping: 41 ms 268.35 GB Logging policy: 2 Weeks	✓ SSL-VPN Connect guide TCP: 1403 UDP: Supported		✓ OpenVPN Config file TCP: 1403 UDP: 1463	✓ MS-SSTP Connect guide SSTP Hostname : vpn169867300.o pengw.net:1403	By c247173069e74cc's own r	508,506
Viet Nam	vpn362434417.opengw.net 58.187.9.15 (adsl-dynamic-pool-xxx.fpt.vn)	3 sessions 1 days Total 4,338 users	18.41 Mbps Ping: 22 ms 15.01 GB Logging policy: 2 Weeks	✓ SSL-VPN Connect guide TCP: 1680 UDP: Supported		✓ OpenVPN Config file TCP: 1680 UDP: 1762	✓ MS-SSTP Connect guide SSTP Hostname : vpn362434417.o pengw.net:1680	By Admin-PC's owner	434,543
United States	vpn559906453.opengw.net 50.135.106.72 (c-50-135-106-72.hsd1.wa.comcast.net)	32 sessions 1 days Total 12,528 users	15.00 Mbps Ping: 17 ms 189.55 GB Logging policy: 2 Weeks	✓ SSL-VPN Connect guide TCP: 1899 UDP: Supported		✓ OpenVPN Config file TCP: 1899 UDP: 1271	✓ MS-SSTP Connect guide SSTP Hostname : vpn559906453.o pengw.net:1899	By MTR-PC's owner	425,217

国・地域

IP / FQDN

状態

速度

対応 VPN フォーム

VPN Gate Client for Windows

- VPN Gate Server にワンクリックで接続
- VPN Gate Server になることもできる (オプション)
(互助)

VPN Gate Academic Experimental Project Plugin for SoftEther VPN Client

VPN Gate Public VPN Relay Servers Academic project at University of Tsukuba, Japan. 筑波大学 University of Tsukuba

Gain freedom access to Internet by using VPN connection via Public VPN Servers provided by volunteers around the world. Bypass your local malfunctioning firewall's packet blocking, and hide your IP address safely.

VPN Gate Academic Web Site

Refresh List

99 Public VPN Relay Servers on the Earth! (Updated at 2014-03-16 15:13:08)

DDNS Hostname	IP Address (Hostname)	Region	Uptime	VPN Sessions	Line Speed	Ping (G)
vpn362434417.opengw....	58.187.9.15 (adsl-dyna...	Viet Nam	1 days	3 sessions	18.4 Mbps	22, 22
vpn694017992.opengw....	175.123.77.38	Korea Republic of	4 hours	5 sessions	63.3 Mbps	64, 64
vpn559906453.opengw....	50.135.106.72 (c-50-1...	United States	1 days	32 sessions	15.0 Mbps	17, 17
vpn493837156.opengw....	1.237.84.65	Korea Republic of	3 days	17 sessions	57.0 Mbps	203, 203
vpn970293128.opengw....	119.26.157.48 (zaq771...	Japan	1 days	3 sessions	28.9 Mbps	169, 169
vpn590682393.opengw....	68.2.175.192 (ip68-2-...	United States	2 hours	13 sessions	23.6 Mbps	61, 61
vpn273730891.opengw....	118.157.74.169 (KD11...	Japan	3 days	213 sessions	127.3 Mbps	57, 57
vpn124876588.opengw....	116.41.118.159	Korea Republic of	1 days	11 sessions	21.4 Mbps	79, 79
vpn948467262.opengw....	218.156.5.15	Korea Republic of	1 days	40 sessions	19.9 Mbps	78, 78
vpn103812839.opengw....	24.188.22.182	United States	2 days	14 sessions	16.2 Mbps	41, 41
vpn845537890.opengw....	122.32.151.204	Korea Republic of	18 hours	3 sessions	19.2 Mbps	57, 57
vpn304580552.opengw....	49.143.21.227	Korea Republic of	3 hours	3 sessions	18.7 Mbps	54, 54
vpn261900721.opengw....	71.58.14.58 (c-71-58-...	United States	2 days	5 sessions	10.4 Mbps	27, 27
vpn733608004.opengw....	182.214.49.67	Korea Republic of	1 hours	3 sessions	12.8 Mbps	58, 58

A VPN Server with higher Line Speed (measured by Mbps) and smaller Ping result are usually more comfortable to use. You might be able to browse websites which are normally unreachable from your area if you use VPN servers that are not in your area.

Proxy Settings Virtual Network Adapter: VPN

Connect to the VPN Server

Implemented as a plug-in for SoftEther VPN. (c) VPN Gate Project at University of Tsukuba, Japan.

VPN Gate Clients for iOS and Android (有志ユーザが自由に作成したもの)

2013年3月8日に公開 http://www.vpngate.net/

VPN Gate
Public VPN Relay Servers

Academic Experiment at University of Tsukuba, Japan.

[VPN Servers List](#) [What is VPN Gate](#) [How to Connect](#) [Download](#) [Join Us](#) [Forum](#) [Mirror Sites](#) [Languages](#)

Follow @vpngate

Free Access to World Knowledge Beyond Government's Firewall.

Your IP: 59x121x46x62.ap59.ftth.uxcom.jp (27.121.46.62)

Your country: Japan
Let's change your IP address by using VPN Gate!

Welcome to VPN Gate. (Launched on March 8, 2013.)

- You can get through your government's firewall to browse restricted websites. (e.g. YouTube.)
- You can disguise your IP address to hide your identity while surfing the Internet.
- You can protect yourself by utilizing the strong encryption while using public Wi-Fi. [More Details...](#)

Supports Windows, Mac, iPhone, iPad and Android.

SoftEther VPN
Supports OpenVPN, L2TP/IPsec and SSL-VPN.
An open-source VPN software development project since March 8.

University of Tsukuba, Japan.
www.softether.org

VPN Gate is based on SoftEther VPN, a multi-protocol VPN server.

Today: 2,105,134 connections, Cumulative: 194,323,808 connections, Traffic: 5,415.22 TB. 194,323,808 VPN connections from 220 Countries.

VPN Session ID	Start time (UTC)	VPN source country	VPN destination country	VPN protocol
VPN-194323808	2014/03/17 4:13:39 (0 mins ago)	Taiwan	Korea Republic of	OpenVPN
VPN-194323807	2014/03/17 4:13:38 (0 mins ago)	China	Korea Republic of	OpenVPN
VPN-194323806	2014/03/17 4:13:30 (0 mins ago)	Taiwan	Korea Republic of	OpenVPN

Rank	Country	Traffic	# Connections
1	Korea Republic of	1,739,641.0 GB	7,238,931
2	China	749,661.0 GB	25,300,088
3	Taiwan	660,454.5 GB	65,672,773

http://www.vpngate.net/en/

中国 GFW 管理局の反応

2013 年 3 月

Sun	Mon	Tue	Wed	Thu	Fri	Sat
					VPN Gate サービス公開	
3	4	サーバリスト上の サーバを手動で 1 つずつ手段	特製自動クロー ラを開発し動作 開始		8	9
10	11	12	13	14	15	16
17	18	19	20	21	22	23
24	25	26	27	28	29	30
31	1	2	3	4	5	6

GFW 管理当局は Python を用いて 急いで VPN Gate クローラを開発

Chinese GFW Authority

**Running
24h
(every 5 mins)**

HTML Crawler
&
Table Parser

HTTP GET

Automatic
IP Blacklist
Update

```
body = Get("http://www.vpngate.net/");  
servers_list = ParseTable(body);  
  
foreach (server_ip in servers_list)  
{  
    firewall.Insert(server_ip);  
}
```

Government's
Black-hole
Router

Country (Physical location)	DNS hostname IP Address (ISP hostname)	VPN sessions Uptime Cumulative users	Line quality Throughput and Ping Cumulative Transfers Logging policy
Japan	vg2018151932.opengw.net 120.74.141.252	100 sessions 1 days Total 42,465 users	33.34 Mbps Ping: 13 ms 3,277.92 GB Logging policy: 2 Weeks
Korea Republic of	1.2.3.4	5 sessions 6 hours Total 518 users	67.10 Mbps Ping: 12 ms 46.65 GB Logging policy: 2 Weeks
United States	5.6.7.8	0 sessions 12 hours Total 88 users	11.95 Mbps Ping: 18 ms 4.38 GB Logging policy: 2 Weeks
Singapore	9.0.1.2	0 sessions 12 hours Total 705 users	11.47 Mbps Ping: 24 ms 6.26 GB Logging policy: 2 Weeks
Viet Nam	vg712346371.opengw.net 42.117.139.9	0 sessions 2 hours Total 307 users	2.69 Mbps Ping: 42 ms 2.12 GB Logging policy:

www.vpngate.net
VPN Gate Servers
List HTML table

VPN Gate リストサーバのアクセスログ

ID	Access Date	Client FQDN	URL	User Agent
3312453	3/23/13 7:40 PM	ec2-23-20-4-19.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3312674	3/23/13 7:41 PM	ec2-50-16-163-135.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3313385	3/23/13 7:45 PM	ec2-23-20-4-19.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3313579	3/23/13 7:46 PM	ec2-50-16-163-135.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3314469	3/23/13 7:50 PM	ec2-23-20-4-19.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3314708	3/23/13 7:51 PM	ec2-50-16-163-135.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3315395	3/23/13 7:55 PM	ec2-23-20-4-19.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3315642	3/23/13 7:56 PM	ec2-50-16-163-135.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3316252	3/23/13 8:00 PM	198-136-27-242.static.gorillaservers.com	http://www.vpngate.net/cn/	Python-urllib/1.17
3316383	3/23/13 8:00 PM	ec2-23-20-4-19.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3316570	3/23/13 8:01 PM	ec2-50-16-163-135.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3317306	3/23/13 8:05 PM	ec2-23-20-4-19.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3317533	3/23/13 8:07 PM	ec2-50-16-163-135.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3318339	3/23/13 8:10 PM	ec2-23-20-4-19.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3318553	3/23/13 8:12 PM	ec2-50-16-163-135.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3319072	3/23/13 8:15 PM	198-136-27-242.static.gorillaservers.com	http://www.vpngate.net/cn/	Python-urllib/1.17
3319236	3/23/13 8:15 PM	ec2-23-20-4-19.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3319480	3/23/13 8:17 PM	ec2-50-16-163-135.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3320192	3/23/13 8:20 PM	ec2-23-20-4-19.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3320439	3/23/13 8:22 PM	ec2-50-16-163-135.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17
3321185	3/23/13 8:26 PM	ec2-23-20-4-19.compute-1.amazonaws.com	http://www.vpngate.net/en/	Python-urllib/1.17

この時点で GFW 管理局は VPN Gate リストサーバの返却するリスト内容を 100% 信用

Chinese GFW Authority

Running
24h
(every 5 mins)

HTML Crawler
&
Table Parser

HTTP GET

Automatic
IP Blacklist
Update

```
body = Get("http://www.vpngate.net/");  
servers_list = ParseTable(body);  
  
foreach (server_ip in servers_list)  
{  
    firewall.Insert(server_ip);  
}
```

Government's
Black-hole
Router

Country (Physical location)	DNS hostname IP Address (ISP hostname)	VPN sessions Uptime Cumulative users	Line quality Throughput and Ping Cumulative Transfers Logging policy
Japan	vg2018151932.opengw.net 120.74.141.252	100 sessions 1 days Total 42,465 users	33.34 Mbps Ping: 13 ms 3,277.92 GB Logging policy: 2 Weeks
Korea Republic of		5 sessions 6 hours Total 518 users	67.10 Mbps Ping: 12 ms 46.65 GB Logging policy: 2 Weeks
United States		0 sessions 12 hours Total 88 users	11.95 Mbps Ping: 18 ms 4.38 GB Logging policy: 2 Weeks
Singapore		0 sessions 12 hours Total 705 users	11.47 Mbps Ping: 24 ms 6.26 GB
Viet Nam			

google public DNS
8.8.8.8

VPN Gate Servers
List HTML table

* この「無実の IP アドレス」は例である。

GFW は VPN Gate のリストサーバに混入した IP アドレスを 30 分以内に自動遮断

From the computer in China:

```
>ping 8.8.8.8
```

```
Pinging google-public-dns-a.google.com [8.8.8.8] with 32 bytes of data:
```

```
Reply from 8.8.8.8: bytes=32 time=159ms TTL=238
```

```
Reply from 8.8.8.8: bytes=32 time=143ms TTL=238
```

```
Reply from 8.8.8.8: bytes=32 time=141ms TTL=238
```

```
Reply from 8.8.8.8: bytes=32 time=148ms TTL=238
```

```
Reply from 8.8.8.8: bytes=32 time=144ms TTL=238
```

```
Request timed out.
```

Great Firewall に、任意の IP アドレスを遮断させる実験に成功した。

* この「無実の IP アドレス」は例である。

GFW 管理局はクローラの機能を強化

2013 年 3 月

協調的スパイ発見手法による 検閲当局の IP アドレスの識別と遮断

ログ分析プログラムによるスパイ発見手法:

1. 短い時間で多数の VPN サーバに接続試行した単一 IP アドレス (または IP サブネット) は、スパイである。
2. VPN サーバへの接続後、ほとんどデータ通信をせずに、または短時間で切断することを繰り返す IP アドレス (サブネット) はスパイである。
3. 上記に加えていくつかの運用的アルゴリズムを組み合わせたり、閾値を調整したりして検出。

2013年4月24日に開始した協 調的スパイ発見手法の効果

Percentages of blocked VPN Gate servers by GFW

なぜ 2013 年 8 月末に GFW は遮断を突然停止させたのか? (仮説)

- 2013 年 8 月末時点では、ボランティアによって、1 日あたり 6,000 個のユニーク IP アドレスが供給されていた。
 - 2,400 台 (40%) のボランティアサーバの IP アドレスは毎日変化した。
 - したがって 17,000 個のユニーク IP アドレスが毎週登場した。

• 推測:

- GFW の遮断
- GFW の推定
- これらの理

にした。

VPN Gate 利用国 ランキング (2021.7)

検閲用ファイアウォール
があるとされている国

www.vpngate.net
でリアルタイム掲載中

全世界からの VPN Gate 利用数 (1 日あたり)

★ 1 日あたり転送データ量:
235,073,074,603,200 bytes (235 TB)

★ 1 日あたり VPN 接続数:
5,497,045 接続 (549 万接続)

VPN Gate は、政府検閲下の市民の
ためのインターネットアクセスの最終保
障手段である。

これらの国の市民の自由なインターネッ
トアクセスの実現と、
政府に偏向されない正しい知識の習得
や自由な経済活動を支えている。

← 「ミャンマー」
ランキング
上昇中

ランキング	国・地域	トラフィック	累積 VPN 接続数
1	Korea Republic of	62,348,895.8 GB	312,750,758
2	Iran (ISLAMIC Republic Of)	45,297,068.6 GB	3,419,781,267
3	United States	26,813,433.6 GB	549,978,796
4	France	24,994,294.0 GB	261,646,797
5	Japan	23,737,041.9 GB	332,576,041
6	Taiwan	23,374,213.7 GB	548,201,296
7	India	20,995,441.7 GB	501,120,246
8	China	20,294,600.5 GB	711,840,741
9	Indonesia	18,268,775.2 GB	645,753,967
10	United Arab Emirates	9,709,908.9 GB	416,108,784
11	Viet Nam	9,562,676.3 GB	250,107,554
12	Thailand	9,378,138.4 GB	254,678,809
13	Russian Federation	7,261,992.4 GB	107,680,700
14	Philippines	6,772,976.3 GB	241,450,695
15	Malaysia	6,406,196.8 GB	89,697,184
16	Turkmenistan	5,956,277.2 GB	107,318,567
17	Hong Kong	5,877,782.5 GB	132,598,786
18	Canada	4,049,599.9 GB	44,902,972
19	Germany	3,900,246.2 GB	120,377,739
20	Saudi Arabia	3,876,359.2 GB	66,244,352
21	Ukraine	3,655,805.6 GB	255,250,610
22	Myanmar	3,419,973.1 GB	103,146,272
23	Iraq	3,189,913.2 GB	178,034,148

日本時間の日中は、ミャンマーからの VPN 接続回数が全体の約 6% を占めるようになった。(2021/07 時点)

VPN-11213118449	2021/07/16 4:05:24 (1 分前)	利用中	1 分間	Myanmar	Japan	118.27.x.x	OpenVPN	利用中
VPN-11213118448	2021/07/16 4:05:24 (1 分前)	利用中	1 分間	Myanmar	Japan	219.100.x.x	OpenVPN	利用中
VPN-11213118447	2021/07/16 4:05:24 (1 分前)	4:06:28	1 分間	Bangladesh	Korea Republic of	121.184.x.x	OpenVPN	6.11 MB
VPN-11213118446	2021/07/16 4:05:24 (1 分前)	4:05:29	0 分間	Taiwan	Japan	116.82.x.x	OpenVPN	0.05 MB
VPN-11213118445	2021/07/16 4:05:24 (1 分前)	利用中	1 分間	Japan	Japan	219.100.x.x	SoftEther VPN (TCP)	利用中
VPN-11213118444	2021/07/16 4:05:24 (1 分前)	利用中	1 分間	Myanmar	Japan	36.2.x.x	OpenVPN	利用中
VPN-11213118443	2021/07/16 4:05:24 (1 分前)	利用中	1 分間	Bangladesh	Japan	219.100.x.x	OpenVPN	利用中
VPN-11213118442	2021/07/16 4:05:24 (1 分前)	利用中	1 分間	India	Korea Republic of	14.42.x.x	OpenVPN	利用中
VPN-11213118441	2021/07/16 4:05:24 (1 分前)	利用中	1 分間	United Arab Emirates	Japan	153.231.x.x	OpenVPN	利用中
VPN-11213118440	2021/07/16 4:05:24 (1 分前)	利用中	1 分間	Iran (ISLAMIC Republic Of)	Japan	219.100.x.x	OpenVPN	利用中
VPN-11213118439	2021/07/16 4:05:23 (1 分前)	利用中	1 分間	Japan	Korea Republic of	211.105.x.x	OpenVPN	利用中
VPN-11213118438	2021/07/16 4:05:23 (1 分前)	利用中	1 分間	Germany	Korea Republic of	118.222.x.x	SoftEther VPN (TCP)	利用中
VPN-11213118437	2021/07/16 4:05:23 (1 分前)	利用中	1 分間	Myanmar	Japan	219.100.x.x	OpenVPN	利用中
VPN-11213118436	2021/07/16 4:05:23 (1 分前)	利用中	1 分間	Bangladesh	Japan	219.100.x.x	OpenVPN	利用中
VPN-11213118435	2021/07/16 4:05:23 (1 分前)	利用中	1 分間	Iran (ISLAMIC Republic Of)	Japan	110.233.x.x	OpenVPN	利用中
VPN-11213118434	2021/07/16 4:05:23 (1 分前)	利用中	1 分間	Taiwan	Japan	219.100.x.x	L2TP/IPsec	利用中
VPN-11213118433	2021/07/16 4:05:23 (1 分前)	利用中	1 分間	India	Japan	219.100.x.x	OpenVPN	利用中
VPN-11213118432	2021/07/16 4:05:23 (1 分前)	利用中	1 分間	Bangladesh	Korea Republic of	121.185.x.x	OpenVPN	利用中
VPN-11213118431	2021/07/16 4:05:23 (1 分前)	利用中	1 分間	Myanmar	Korea Republic of	110.14.x.x	OpenVPN	利用中
VPN-11213118430	2021/07/16 4:05:23 (1 分前)	利用中	1 分間	Myanmar	United States	71.121.x.x	OpenVPN	利用中

(参考: 2013 年のランキング。ミャンマーはランク外であった)

Rank	Country	Traffic	# Users
1	Korea Republic of	43,240.0 GB	147,411
2	China	37,751.7 GB	759,597
3	United States	30,198.5 GB	116,493
4	Iran (ISLAMIC Republic Of)	19,964.8 GB	787,890
5	Japan	15,530.4 GB	257,454
6	India	7,020.6 GB	185,847
7	Taiwan	6,378.2 GB	113,646
8	France	4,038.0 GB	24,786
9	Canada	3,853.7 GB	17,068
10	Viet Nam	3,505.2 GB	139,177
11	United Kingdom	3,267.2 GB	21,471
12	Malaysia	2,602.7 GB	48,726
13	Singapore	2,522.5 GB	16,844
14	Spain	1,927.1 GB	11,714
15	Hong Kong	1,779.9 GB	31,919
16	Australia	1,704.5 GB	13,024
17	Saudi Arabia	1,012.9 GB	5,124
18	Thailand	917.3 GB	11,489
19	United Arab Emirates	888.6 GB	7,334
20	Indonesia	806.9 GB	24,658
21	Greece	765.9 GB	1,278
22	Germany	765.6 GB	8,257
23	Russian Federation	689.5 GB	11,339
24	Netherlands	604.5 GB	16,437
25	Portugal	570.1 GB	1,016

26	Pakistan	497.3 GB	5,653
27	Philippines	471.1 GB	24,035
28	Turkey	272.7 GB	2,587
29	Italy	254.3 GB	4,072
30	Mexico	216.0 GB	5,420
31	Brazil	204.7 GB	2,961
32	Romania	199.0 GB	2,021
33	New Zealand	198.2 GB	1,877
34	Syrian Arab Republic	195.8 GB	13,207
35	Switzerland	181.1 GB	1,765
36	Ukraine	180.6 GB	4,282
37	Ireland	173.4 GB	2,280
38	Argentina	169.5 GB	6,936
39	Poland	163.5 GB	14,142
40	Chile	156.3 GB	2,325
41	Finland	153.4 GB	687
42	Belgium	150.1 GB	1,641
43	Czech Republic	138.3 GB	2,229
44	Qatar	129.6 GB	1,520
45	Uganda	122.7 GB	33,767
46	Nigeria	117.3 GB	6,217
47	Tanzania United Republic of	115.3 GB	707
48	Denmark	112.1 GB	766
49	Sweden	103.6 GB	1,444
50	Morocco	92.8 GB	1,790

51	Oman		
52	Cambodia		
53	Macau		
54	Estonia		
55	South Africa		
56	Bulgaria		
57	Korea Democratic People's Republic		
58	Bangladesh		
59	Bahamas		
60	Cote D'ivoire		
61	Peru		
62	Hungary		
63	Ghana		
64	Slovakia (SLOVAK Republic)		
65	Norway		
66	Egypt		
67	Austria		
68	Colombia		
69	Vanuatu		
70	Ecuador		
71	Trinidad and Tobago		
72	Tunisia		
73	Venezuela		
74	Kazakhstan		
75	Israel		

VPN Gate のまとめ

VPN Gate は以下の 3 つの手法を用いて検閲用ファイアウォールに対する遮断耐性を実現

1. 頻繁に変化する大量の IP アドレスを用いる。
(ボランティアベースのシステム)
2. 検閲当局に対して、遮断前に IP アドレスでの VPN サーバ動作有無の検証を強いる。
(無実の IP アドレス混入手法)
3. 検閲当局が VPN サーバ動作有無の検証をできなくする。
(協調的スパイ発見手法)

第3章 偉大なる中国 GFW エンジニアたちの優れた研究開発能力 - VPN Gate 論文発表後の GFW の進化 -

と新たな遮断手法への対抗

2014年4月3日論文発表 (NSDI 2014 シアトル)

VPN Gate: A Volunteer-Organized Public VPN Relay System with Blocking Resistance for Bypassing Government Censorship Firewalls

Operational Systems Track

Daiyuu Nobori and Yasushi Shinjo

Department of Computer Science, University of Tsukuba, Japan

Abstract

VPN Gate is a public VPN relay service designed to achieve blocking resistance to censorship firewalls such as the Great Firewall (GFW) of China. To achieve such resistance, we organize many volunteers to provide a VPN relay service, with many changing IP addresses. To block VPN Gate with their firewalls, censorship authorities must find the IP addresses of all the volunteers. To prevent this, we adopted two techniques to improve blocking resistance. The first technique is to mix a number of innocent IP addresses into the relay server list provided to the public. The second technique is collaborative spy detection. The volunteer servers work together to create a list of spies, meaning the computers used by censorship authorities to probe the volunteer servers. Using this list, each volunteer server ignores packets from spies. We launched VPN Gate on March 8, 2013. By the end of August it had about 3,000 daily volunteers using 6,300 unique IP addresses to facilitate 464,000 VPN connections from users worldwide, including 45,000 connections and 9,000 unique IP addresses from China. At the time VPN Gate maintained about 70% of volunteer VPN servers as unblocked by the GFW.

1. Introduction

Some countries in the world have censorship firewalls operated by their governments to prohibit access to servers in foreign countries. For instance, the Great Firewall (GFW) of China blocks access to Twitter, Facebook, and YouTube. Internet users in countries subject to censorship often use overseas public relay servers to bypass censorship firewalls. Public proxies, VPN servers, and Tor nodes [7] are popular examples of such relay servers. Usually, the IP addresses of relay servers are publically available for user convenience. A censorship authority can easily block these relays, however, by adding the IP addresses to its firewall blocking list. Moreover, the Chinese authority, in particular, scans for unlisted Tor nodes and blocks them automatically [19]. Tor relays currently have no blocking resistance [12] against such scanning activities.

In this research, we have built a public VPN relay server system with blocking resistance to censorship

firewalls such as the GFW. We call this system VPN Gate. To achieve blocking resistance, VPN Gate uses frequently changing IP addresses that are provided by volunteers. The central list server, called the *VPN Gate List Server*, manages a list of the IP addresses of all active VPN servers. We call this list the *Server List*. A user can get only part of the Server List and connect his/her PC to an active VPN server in the list. The user can then communicate with blocked Internet servers through the active VPN server. It is hard for a censorship authority to block all the active VPN servers in VPN Gate.

It is important for anti-censorship systems to achieve blocking resistance. We adopted two techniques for blocking resistance: innocent IP mixing and collaborative spy detection. In innocent IP mixing, we include a number of IP addresses, which are unrelated to VPN Gate, in the Server List. For instance, we include vitally important servers (e.g., Windows Update servers). This technique forces a censorship authority to remove innocent IP addresses from the Server List before adding addresses to the firewall blocking list. The second technique, collaborative spy detection, seeks probing activities from censorship authority's computers, called *spies*. In this technique all the volunteer VPN servers work together to create a source IP address list of spies, called the *Spy List*, and they ignore probing packets from spies. This technique makes the authority unable to distinguish between the IP addresses of active VPN servers and innocent IP addresses or those of inactive VPN servers.

The VPN Gate system consists of instances of the VPN Gate Server software, an optional application, the VPN Gate Client software, and a central List Server. Volunteers can easily install and execute VPN Gate Server. For instance, volunteers don't have to configure Network Address Translation (NAT) boxes to open TCP/UDP ports. Users can connect to VPN Gate Server with a Secure Sockets Layer (SSL)-VPN protocol by using VPN Gate Client. Users can also connect to a VPN server with the L2TP/IPsec, OpenVPN, and MS-SSTP protocols by using the built-in, OS-provided VPN clients on PCs and smartphones. As for the third piece of the system, our research group runs the VPN Gate List Server which accepts registration from volunteer servers, generates the Server List, and distributes it to users.

2014年6月頃 中国 GFW が機能強化

- 従来の GFW の提供サービス
 - ブラックリストに入っている海外 IP アドレス宛の通信を常時ブロックする
 - 数千 IP アドレスが上限
- 新たな GFW の提供サービス
 - ブラックリストに入っている海外 IP アドレス宛の通信が発生したらその後 180 秒だけブロックする
 - 上限がなくなった！

2014年8月頃～ スキャナーが改良された

- いつスキャンされているのかどうかよく分からない
- どんどんブロックされるようになった
- VPN Gate 側での暫定対策
 - スキャナーの packets (TLS Client Hello) の特徴を見分けてスキャナーからの packets の場合無視する

インチキ 見分け方

- 以下のパケットがきたら GFW のスキャナーである！

[始まり]

16 03 01

[終わり]

00 06 00 03 02 01 00

00 ff 01 00 00 04 00 23 00 00

filtered.pcap

File Edit View Go Capture Analyze Statistics Telephony Tools Internals Help

Filter: Expression... Clear Apply Save

No.	Time	Source	Destination	Protocol	Len	Info
52	23:32:03.606495	211.65.205.0	220.216.107.77	TCP	66	59135 > 443 [AC
53	23:32:03.607188	211.65.205.0	220.216.107.77	TLSv1	160	Client Hello
54	23:32:03.629067	220.216.107.77	218.10.62.249	NBNS	92	Name query NBST
55	23:32:03.629069	220.216.107.77	218.10.62.249	NBNS	92	Name query NBST
56	23:32:03.629074	220.216.107.77	218.10.62.249	NBNS	92	Name query NBST
57	23:32:03.660290	220.216.107.77	211.65.205.0	TCP	66	443 > 59135 [AC
58	23:32:03.755487	220.216.107.77	218.10.62.249	TCP	60	443 > 32954 [RS

Frame 53: 160 bytes on wire (1280 bits), 160 bytes captured (1280 bits)

- Ethernet II, Src: Cisco_16:42:c0 (00:18:74:16:42:c0), Dst: 4c:4e:35:a6:3a:51 (4c:4e:35:a6:3a:51)
- Internet Protocol Version 4, Src: 211.65.205.0 (211.65.205.0), Dst: 220.216.107.77 (220.216.107.77)
- Transmission Control Protocol, Src Port: 59135 (59135), Dst Port: 443 (443), Seq: 1227470597, Ack: 778562874, Len: 94
- Secure Sockets Layer
 - TLSv1 Record Layer: Handshake Protocol: Client Hello
 - Content Type: Handshake (22)
 - Version: TLS 1.0 (0x0301)
 - Length: 89
 - Handshake Protocol: Client Hello
 - Handshake Type: Client Hello (1)
 - Length: 85
 - Version: TLS 1.0 (0x0301)
 - Random
 - Session ID Length: 0
 - Cipher Suites Length: 40
 - Cipher Suites (20 suites)
 - Compression Methods Length: 1
 - Compression Methods (1 method)
 - Extensions Length: 4
 - Extension: SessionTicket TLS
 - Type: SessionTicket TLS (0x0023)
 - Length: 0
 - Data (0 bytes)

```

0000 4c 4e 35 a6 3a 51 00 18 74 16 42 c0 08 00 45 00  LN5.:Q.. t.B...E.
0010 00 92 b9 28 40 00 26 06 b2 d5 d3 41 cd 00 dc d8  ...(@.&. ...A...
0020 6b 4d e6 ff 01 bb 49 29 b7 05 2e 67 ed 3a 80 18  km...I) ...g...
0030 00 5c a1 c9 00 00 01 01 08 0a 06 6a 0e 46 02 b1  .\..... ]..F..
0040 9d f0 16 03 01 00 59 01 00 00 55 03 01 53 f8 a5  ....Y...U..S..
0050 e3 0d 0c e1 5c 64 a4 dd 3c 8d 12 35 4e e2 0b 59  ....\d...<..5N..Y
0060 12 3f 7f 52 fa 62 27 83 23 9e 77 7c 86 00 00 28  .?.R.b'. #.w|... (
0070 00 39 00 28 00 25 00 16 00 12 00 03 00 22 00 22  .9.8.5... ..3.2
0080 00 2f 00 05 00 04 00 15 00 12 00 09 00 14 00 11  ./. .... ..
0090 00 08 00 06 00 03 00 ff 01 00 00 04 00 23 00 00  ..... ..#.
  
```

Length of hello extensions (ssl.handshake.extensions_length), 2 bytes

Packets: 103 Displayed: 103 Ma... ..

「东南大学」でスキャナーを開発しているのかな？

```
C:\Windows\system32\cmd.exe
% [whois.apnic.net]
% Whois data copyright terms http://www.apnic.net/db/dbcopyright.html

% Information related to '211.65.192.0 - 211.65.207.255'

inetnum:      211.65.192.0 - 211.65.207.255
netname:      JSERNETB-CN
descr:        ~[=-KUJ!=LS]:M?FQP<FKc;zMx~]
descr:        Jiangsu Province Education & Reseach Network
descr:        South East University, Nanjing, Jiangsu 210096, China
country:      CN
admin-c:      JG258-AP
tech-c:       JG258-AP
notify:       address-allocation-staff@net.edu.cn
mnt-by:       MAINT-CERNET-AP
status:       ASSIGNED NON-PORTABLE
changed:      hostmaster@net.edu.cn 20000530
changed:      hm-changed@apnic.net 20040927
source:       APNIC

person:       Jian Gong
address:      Southeast University
address:      Department of Computer Science and Engineering
address:      Nanjing 210096
country:      CN
phone:        +86-25-3614718
phone:        +86-25-3617335
e-mail:       jgong@cs.seu.edu.cn
nic-hdl:      JG258-AP
notify:       dbmon@apnic.net
mnt-by:       MAINT-NULL
changed:      hostmaster@apnic.net 19960206
changed:      hm-changed@apnic.net 20040927
source:       APNIC

% This query was served by the APNIC Whois Service version 1.69.1-APNICv1r2 (WHOIS3)
```

GFWインチキ暫定対策の欠点:

- 暫定対策をしているのが GFW の技術者にバレたらスキャナーを改良されてしまう
- そこで:

GFW 最大の弱点:

国内通信はブロックできない

2015年1月～ 反撃開発開始

- P2P 通信の実装
中国国内の VPN Gate Client を多段ホップして海外のサーバーに接続する
- 多段ホップの最終目的地である海外のサーバーの IP アドレスは秘匿する
(Server List に載せない)
 - GFW スキャナーによるスキャン対象にならない
 - SSL セッション接続後に共通鍵を提示しないと VPN サーバーとして動作しない
(普通の HTTPS サーバーに見せかける)

VPN Gate Client P2P Relay

- NAT 透過
 - UDP Hole Punching
 - Universal Plug and Play (TCP or UDP)
- バックグラウンドで動作
 - 中国国内で動作していると自己判断した場合にのみ稼働

2015年1月31日 P2P 機能搭載版 VPN Gate Client 配布開始

Download

VPN Gate Client download (for Windows, freeware)

Simply install VPN Gate Client Plugin to SoftEther VPN Client. It will enable you to connect to any of our Public VPN Relay Servers of VPN Gate in a snap. It has a better throughput than L2TP, OpenVPN or SSTP. This program files are digitally signed by a certificate issued by GlobalSign. The binary file has a countersignature issued by Symantec.

➤ Download SoftEther VPN Client + VPN Gate Client Plugin

[vpngate-client-2015.02.26-build-9530.131940.zip](#)

Languages available: English, Japanese and Simplified Chinese

Compatible OS: Windows, CPU: Intel x86 and x64

(Windows 98 SE / ME / 2000 SP4 / XP SP2, SP3 / Server 2003 SP2 / Vista SP1, SP2 / Server 2008 SP1, SP2 / Hyper-V Server 2008 / 7 SP1 / Server 2008 R2 SP1 / Hyper-V Server 2008 R2 / 8 / Server 2012 / Hyper-V Server 2012)

➤ Download VPN Gate Client from CNET Download.com

You can download SoftEther VPN Client + VPN Gate Client Plugin directly from us, or from the World's most popular download site -- Download.com by CNET. You may try using CNET Download.com if you cannot download from our primary download server.

IMPORTANT NOTICES (インストール時に表示)

5.13. The P2P Relay Function in the VPN Gate Client to strengthen the capability of circumvention of censorship firewalls

VPN Gate Clients, which are published since January 2015, include the P2P Relay Function. The P2P Relay Function is implemented in order to strengthen the capability of circumvention of censorship firewalls. If the P2P Relay Function in your VPN Gate Client is enabled, then the P2P Relay Function will accept the

5.13. VPN Gate 客户端的 P2P 中继功能可加强针对防火墙管控的规避能力

P2P 中继功能是为了加强规避防火墙管控的能力。如果 P2P 中继功能在您的 VPN Gate 客户端被启用，那么 P2P 中继功能将接受来自 VPN Gate 用户的 VPN 连接，提供中继功能给外部远程 VPN Gate 的服务 器，这是由第三方在免费的互联网环境下托管的。此 P2P 中继功能从来不提供共享 NAT 功能，也不更换

5.13. VPN Gate Client に組み込まれている検閲用ファイアウォールの回避のための P2P 中継機能について
2015 年 1 月以降にリリースされた VPN Gate Client には P2P 中継機能が搭載されています。この P2P 中継機能は検閲用ファイアウォールの回避の強化を目的としています。あなたの VPN Gate Client で P2P 中継機能が有効となっている場合は、P2P 中継機能は、専らあなたと同じ地域に居住する他の VPN Gate のユーザーからの VPN

VPN Gate 公共 VPN 中继服务器

通过使用 VPN 连接经由全世界志愿者提供的公共 VPN 服务器获得自由访问互联网。绕过您的本地故障防火墙的数据包拦截，并安全地隐藏您的 IP 地址。

在这个地球上的 97 个公共 VPN 中继服务器！(更新于 2015-02-26 22:49:05)

DDNS 唯一主机名	IP 地址 (主机名)	国家/地区	运行时间	VPN 会话	线路速度	Ping (G...	SSL-VPN (TCP)	UDP 支持	日志策略	累积转移	累计用户	操作员的名字
vpn922405375.opengw...	49.80.252.194	Japan	9 天	23 会话	36.1 Mbps	62, 62	-	UDP OK	两周	4,942,403,315 bytes	469 登录次数	索尼大法好's owner - P2P
vpn886660497.opengw...	122.238.189.254	Japan	3 小时	1 会话	26.5 Mbps	70, 70	-	UDP OK	两周	7,673,355,808 bytes	292 登录次数	99b75ec0d6a74b8's owner - P2P
vpn279466212.opengw...	183.193.127.205	Japan	11 小时	0 会话	22.1 Mbps	74, 74	1318	UDP OK	两周	1,321,920,031 bytes	36 登录次数	WIN7-20140721EX's owner - P2P
vpn650736336.opengw...	180.157.215.6	Japan	9 小时	0 会话	23.2 Mbps	137, 137	1386	UDP OK	两周	798,160,634 bytes	55 登录次数	e3's owner - P2P
vpn143075591.opengw...	221.221.189.204	Japan	8 小时	10 会话	22.0 Mbps	141, 141	1632	UDP OK	两周	1,786,852,217 bytes	84 登录次数	RICKDOM-PC's owner - P2P
vpn460203434.opengw...	116.83.85.26 (ntkngw...	Japan	3 分钟	8 会话	67.3 Mbps	8, 8	1410	-	两周	3,281,987,618,615 bytes	59,203 登录次数	hashimoto-PC's owner
vpn959105514.opengw...	116.224.145.123	Japan	9 天	8 会话	15.6 Mbps	87, 87	1924	UDP OK	两周	333,268,502 bytes	29 登录次数	KK's owner - P2P
vpn913221189.opengw...	14.209.159.81	Japan	11 小时	4 会话	12.5 Mbps	46, 46	1969	UDP OK	两周	46,042,513 bytes	5 登录次数	LENOVO's owner - P2P
vpn552019379.opengw...	117.170.11.103	Japan	9 小时	0 会话	13.5 Mbps	57, 57	1344	UDP OK	两周	440,121,506 bytes	58 登录次数	Desmond-PC's owner - P2P
vpn527452988.opengw...	27.204.65.46	Japan	14 小时	3 会话	12.9 Mbps	93, 93	995, 465, 1195, 186...	UDP OK	两周	120,270,696 bytes	7 登录次数	Darkflames-PC's owner - P2P
vpn907507939.opengw...	42.203.196.156	Japan	2 小时	0 会话	15.1 Mbps	127, 127	-	UDP OK	两周	200,686,980 bytes	4 登录次数	PC-20141009DQYT's owner - P2P
vpn815296656.opengw...	210.126.52.169	Korea Re...	3 小时	3 会话	43.7 Mbps	32, 32	1770	UDP OK	两周	113,614,231,316 bytes	2,886 登录次数	win-PC's owner
vpn778582322.opengw...	114.89.59.220	Japan	2 小时	0 会话	12.5 Mbps	88, 88	1976	UDP OK	两周	19,759,199 bytes	6 登录次数	QQ's owner - P2P
vpn718465820.opengw...	211.58.28.64	Korea Re...	20 小时	3 会话	47.4 Mbps	33, 33	1368	UDP OK	两周	114,740,288,399 bytes	664 登录次数	보험회사트북's owner
vpn974631764.opengw...	221.20.14.15 (softban...	Japan	36 分钟	8 会话	23.3 Mbps	17, 17	1365	UDP OK	两周	384,389,333,209 bytes	9,986 登录次数	owner-PC's owner
vpn533609551.opengw...	112.187.139.146	Korea Re...	3 小时	2 会话	45.3 Mbps	34, 34	1459	UDP OK	两周	1,270,701,915,422 bytes	27,563 登录次数	MSDN-SPECIAL's owner
vpn842527117.opengw...	110.12.128.9	Korea Re...	4 小时	0 会话	36.6 Mbps	35, 35	1267	UDP OK	两周	1,865,131,614,986 bytes	48,698 登录次数	Clearbible's owner
vpn441474778.opengw...	14.53.44.41	Korea Re...	13 小时	19 会话	39.0 Mbps	39, 39	995, 465, 1195, 162...	UDP OK	两周	1,737,504,587,262 bytes	71,907 登录次数	jds-16f29a85057's owner
vpn999386588.opengw...	211.226.214.100	Korea Re...	13 小时	2 会话	28.8 Mbps	32, 32	995, 465, 1195, 124...	UDP OK	两周	890,578,467,941 bytes	11,859 登录次数	user-PC's owner
vpn253476154.opengw...	112.64.61.196	Japan	6 天	4 会话	13.7 Mbps	160, 160	-	UDP OK	两周	24,251,870,344 bytes	881 登录次数	Mafuyu's owner - P2P
vpn545029428.opengw...	125.142.111.217	Korea Re...	6 小时	2 会话	53.4 Mbps	39, 39	1862	UDP OK	两周	372,799,500,169 bytes	8,088 登录次数	LEE-PC's owner
vpn783330324.opengw...	61.41.207.194	Korea Re...	1 小时	0 会话	33.2 Mbps	41, 41	1842	UDP OK	两周	262,787,521,974 bytes	24,165 登录次数	
vpn382270593.opengw...	121.10.83.141	Japan	4 小时	1 会话	5.3 Mbps	45, 45	1867	UDP OK	两周	615,061,693 bytes	105 登录次数	Dell-Inspiron's owner - P2P
vpn715163408.opengw...	27.218.137.255	Japan	1 小时	0 会话	9.9 Mbps	121, 121	1848	-	两周	598,371,558 bytes	10 登录次数	wys-PC's owner - P2P
vpn698183203.opengw...	211.49.12.139	Korea Re...	4 小时	0 会话	55.7 Mbps	47, 47	1619	UDP OK	两周	144,954,310,900 bytes	8,043 登录次数	Rein-PC's owner
vpn943111165.opengw...	113.128.116.120	Japan	1 天	0 会话	7.7 Mbps	95, 95	1928	UDP OK	两周	306,546,766 bytes	25 登录次数	WIN-K8NIHIP5GE0's owner - P2P
vpn462709828.opengw...	114.80.246.253	Japan	1 天	1 会话	7.4 Mbps	92, 92	995, 465, 1195, 158...	UDP OK	两周	10,137,943,358 bytes	594 登录次数	hkc-baa244ebcb3's owner - P2P
vpn433500689.opengw...	112.10.69.181	Japan	7 小时	0 会话	7.7 Mbps	64, 64	-	UDP OK	两周	156,882,246 bytes	41 登录次数	HiLeo-PC's owner - P2P
vpn282865415.opengw...	121.166.211.158	Korea Re...	7 小时	5 会话	25.1 Mbps	32, 32	995, 465, 1195, 123...	UDP OK	两周	86,013,644,511 bytes	3,738 登录次数	Dong-PC's owner
vpn943111165.opengw...	183.223.192.107	Japan	13 小时	0 会话	5.2 Mbps	73, 73	1649	UDP OK	两周	574,968,593 bytes	18 登录次数	SKY-20150109NBH's owner - P2P
vpn283053873.opengw...	61.171.250.250	Japan	5 小时	0 会话	6.7 Mbps	74, 74	-	UDP OK	两周	7,269,104,460 bytes	278 登录次数	WJKHLQ5UWN1WZTP's owner - P2P
vpn417959981.opengw...	58.251.202.60	Japan	9 小时	0 会话	7.2 Mbps	135, 135	1935	UDP OK	两周	1,001,039,192 bytes	125 登录次数	RogerEee-PC's owner - P2P
vpn591156302.opengw...	124.237.167.64	Japan	4 小时	0 会话	6.5 Mbps	78, 78	-	UDP OK	两周	88,962,106 bytes	4 登录次数	zyq-PC's owner - P2P
vpn936306808.opengw...	119.108.235.66	Japan	12 小时	1 会话	7.9 Mbps	157, 157	-	UDP OK	两周	121,923,950 bytes	4 登录次数	admin-PC's owner - P2P
vpn811636424.opengw...	182.207.191.140	Japan	3 小时	2 会话	3.9 Mbps	89, 89	1416	UDP OK	两周	232,514,670 bytes	19 登录次数	LENOVO-37D07877's owner - P2P

累计用户	操作员的名字
469 登录次数	索尼大法好's owner - P2P
292 登录次数	99b75ec0d6a74b8's owner - P2P
36 登录次数	WIN7-20140721EX's owner - P2P
55 登录次数	e3's owner - P2P
84 登录次数	RICKDOM-PC's owner - P2P
59,203 登录次数	hashimoto-PC's owner
29 登录次数	KK's owner - P2P
5 登录次数	LENOVO's owner - P2P
58 登录次数	Desmond-PC's owner - P2P
7 登录次数	Darkflames-PC's owner - P2P
4 登录次数	PC-20141009DQYT's owner - P2P
2,886 登录次数	win-PC's owner
6 登录次数	00's owner - P2P

在这个地球上的 97 公共 VPN 中继服务器！(更新于 2019-02-26 22:49:05)

DDNS 唯一主机名	IP 地址 (主机名)	国家/地区	运行时间	VPN 会话	线路速度
vpn922405375.opengw...	49.80.252.194	Japan	9 天	23 会话	36.1 Mbps
vpn886660497.opengw...	122.238.189.254	Japan	3 小时	1 会话	26.5 Mbps
vpn279466212.opengw...	183.193.127.205	Japan	11 小时	0 会话	22.1 Mbps
vpn650736336.opengw...	180.157.215.6	Japan	9 小时	0 会话	23.2 Mbps
vpn143075591.opengw...	221.221.189.204	Japan	8 小时	10 会话	22.0 Mbps
vpn460203434.opengw...	116.83.85.26 (ntkngw..	Japan	3 分钟	8 会话	67.3 Mbps
vpn959105514.opengw...	116.224.145.123	Japan	9 天	8 会话	15.6 Mbps
vpn913221189.opengw...	14.209.159.81	Japan	11 小时	4 会话	12.5 Mbps

P2P Relay 実験の結果

中国国内の P2P Relay 数 400 ~ 1600 台程度

中国国内の P2P Relay を通る VPN セッション数 200 ~ 1200 程度

P2P Relay 経由トラフィック

まとめ・今後の課題

- P2P Relay の実装により GFW による遮断は大幅に困難になった。
- P2P Relay の安定性や性能を評価する。
- GFW 暫定対策がうまくいかなかったら中国国内からの通信はすべて P2P Relay 経由にする。
- **けしからん (素晴らしい) 中国の GFW 当局に雇用されている技術者 (大学院生等) との交流や共同研究を実現する。**

外国政府による けしからん (素晴らしい) インターネット検閲システム (GFW 等) に対抗すれば、双方の技術力が進歩して大変良い

如果日本以外的政府建立了GFW这样的审查系统，而我们日本人建立了反制系统，那么两国的网络技术将迅速进步，这是一件非常好的事情。

Bypassing Government's Censorship Firewall: A Great Firewall Cat-and-Mouse Game in Cyberspace.

2021/07/16 JANOG48 Meeting - インターネット(遮)断

登大遊 (Daiyuu Nobori, Ph.D.)

- 本日の発表内容は、登が2012年～2015年ごろに筑波大学で行っていた研究をベースとしています。少し古い内容ですが、ご了承をお願いします。
- 本研究は、独立した研究者の活動であり、私が現在所属している各組織の立場とは無関係です。